

Camp and Cabin Series Material List

FLOOR SYSTEM

Sills: 2x6 PTSYP (graded #1 Pressure Treated Southern Yellow Pine)

Girders: 2x8 built up on job

Double headers: 2x8 spruce

Felt paper: To cover double headers and sills

Floor joists: 2x8 spruce 16" O.C. (On Center)

Hardware: Floor joist hangers; metal cross bridging

Subfloor: 5/8" T&G (Tongue & Groove) OSB (Oriented Strand Board)

Porch and deck flooring: 5/4x6 radius edge PTSYP

Porch and deck framing: Floor joists, sills, and headers, 2x6 PTSYP

Porch posts



EXTERIOR WALLS

Wall and gable logs: Eastern White Pine, Camp and Cabin grade, milled 6x8 "D" shaped tongue and groove pre-cut and numbered logs, kiln dried. Camp and Cabin grade logs have imperfections and a more rustic look

Log Sealants: Puttylastic caulking; foam gaskets; pre-compressed corner pads; 12" spiral spikes

Window and door jambs: Specially-milled pine with 9" screws

Log siding: Milled ship-lap log siding as needed for floor frame skirting. Eastern White Pine, kiln dried

Wall braces: 6x6 or 6x8 as required with hardware

Splined posts: Specially milled 6x6 as required with hardware

2 sets of construction documents

Construction manual



CEILING

Ceiling joists: 2x8 spruce 16" O.C.

Hardware: Ceiling joist hangers; metal cross bridging

Floor: 5/8" T&G OSB

Posts and beams: Pine, spruce, or LVL (laminated veneer lumber) as required with hardware



ROOF

Double plate on top of log

Roof rafters: 2x8 spruce 16" O.C.

Ridge beam*: LVL

Ridge beam support: 6x6 pine or spruce post; ridge to post connectors; rafter and heel connectors*

Roof sheathing: 5/8" square edge OSB

Fascia: 1" pine boards

Soffits: 1" knotty pine v-match boards

Porch rafters: 2x6 spruce 16" O.C.

Porch beam: 6x6 spruce

Vents: Ridge and soffit

* required for any building over 16' wide

WINDOWS AND EXTERIOR DOORS

Windows: Andersen® 400 Series Low-E4 glass Tilt-Wash double-hung and Casement windows with full screens. Flexi frames

Gliding Patio Doors: Andersen 400 Series Low-E4 Frenchwood® with screens, hardware and locksets

Exterior doors: 3'0"x6'8" pre-hung Therma-Tru® Smooth-Star® fiberglass door system, 20 year limited warranty

Exterior locksets

Backer rod

Exterior window and door trim: Random length pine specially milled 2x4 radius edges

OPTIONAL MATERIALS

Extra log rows

1 1/2" LogHog Screws

Interior wall framing material

1" knotty pine v-match boards for sheathing of interior roof, wall framing, ceiling, and interior window and door trim

Interior doors: Solid pine with raised panel interior doors, pre-hung or sliding with hardware and interior locksets as required

4x8 spruce exposed beam ceiling joists with hangers and 2" v-match loft flooring

AdvanTech® subflooring and roof sheathing

Andersen® window products: optional HeatLock glazing

Engineer Stamped Plans and Energy Calcs