

2024 Premier Series Classic Post & Beam Materials List



First Floor System

- ♦ Pressure-treated sill, 2"x10" spruce floor joists and headers, metal cross bridging and joist hangers
- ♦ 3/4" T&G (Tongue & Groove) AdvanTech® subfloor
- ♦ 2"x12" basement stair stringers

Porch, Deck, and Balcony Materials

- ♦ Pressure-treated nailer, sill, headers, and floor joists; metal cross bridging and joist hangers
- ♦ 5/4"Radius Edge PTSYP decking
- ♦ 6"x6" pine porch posts
- ◆ Spruce rafters, ties, nailers, headers, and metal hangers
- ♦ 5/8" AdvanTech® roof sheathing
- ♦ 1" knotty pine v-groove ceiling boards

Pre-cut Timber Frame System

- ◆ Pre-cut and numbered Eastern White Pine Frame, including: 6"x6" and 6"x8" posts, girts, headers, and principal rafters; 4"x6" straight corner braces
- ◆ Pre-cut and numbered Spruce ceiling joists, posts, beams, roof purlins, blocking, and structural ridge beams
- ◆ Pre-cut, pre-drilled, and numbered Spruce Timber Roof supports beam trusses, with visible steel gusset plates and hardware at cathedral ceiling areas
- ♦ Lag screws, carriage bolts, timber screws, ring shank nails, and tie plates to secure Timber Frame system
- ♦ Decorative wood pegs to conceal fasteners

Structural Insulated Panel System

- ♦ Structural Insulated Panels (SIP's). Panels are fabricated w/ 3 1/2" of urethane foam, injected between two layers of 7/16" OSB (oriented strand board). Each panel is equipped with a built-in wire chase and a tongue & groove edge with a patented cam-lock installation system. Panels are pre-cut for all window and door openings plus all eave and gable cuts, and then numbered for easy installation
- ♦ Urethane foam sealant for all panel joints; 8" screws to secure panels to Timber Frame

Ceiling System

- ♦ 1" knotty pine v-groove ceiling boards: for underside of pre-built flat, vaulted and/or attic truss rafters
- ♦ Beam Ceiling in areas with a second story loft and/or living space above: 4x8 spruce ceiling joists w/joist hangers as required and 2" T&G v-groove flooring

Double Roof System

- ♦ 1" knotty pine v-groove roof boards
- ♦ 2"x 3" spruce roof strapping 24" o.c.
- ♦ 5/8" T&G (Tongue & Groove) AdvanTech® roof sheathing
- ♦ Ridge vent and continuous aluminum strip vents
- ♦ Purlin screws
- ♦ Roof strapping screws

NOTE-Always refer to <u>your</u> individual price quote and Signed Order Form for specific material supplied with your home design.

Interior Partitions, Stairs, and Flooring

- ♦ Spruce studs, plates, shoes, headers, and beam blocking for all interior partitions
- ♦ 2"x12" second floor stair stringers
- ♦ 2"x6" v-groove second floor decking
- ♦ 1" knotty pine v-groove ceiling boards where required

Windows and Doors

- ♦ Interior doors, pre-hung, six panel, pine with Schlage® locksets with standard and custom finishes. Closet door hardware includes: sliding, bi-fold, pre-hung hinged and/or pocket
- ◆ Therma-Tru® Classic-Craft® & Smooth Star® fiberglass exterior doors, insulated and pre-hung with Schlage® locksets with standard and custom finishes
- ♦ Andersen® gliding and hinged patio doors, complete with screen, lockset, and extension jambs when required. Colors: White, Terratone, Sandtone, Forest Green, Black, Canvas, and Dark Bronze
- ♦ Andersen® 400 Series Low-E4 Tilt-Wash double hung, casement, and awning windows w/ full screens. Casement and awning windows are supplied with hand cranks where applicable. Colors: White, Terratone, Sandtone, Forest Green, Black, Canvas, and Dark Bronze
- ♦ Andersen® specialty windows

Garage

- ♦ Exterior wall Framing material, 2" x 6" studs;nailers, plates, headers, shoes, and pressure-treated sills
- ♦7/16" OSB wall sheathing
- ♦ Roof Framing: conventional rafter materials or pre-built truss rafters per plan; 5/8" AdvanTech® roof sheathing
- ♦ Windows and doors per plan

Optional Materials

- ♦ Composite Decking for porches, decks, and balconies
- ♦ Fraser Wood Products[™] pre-finished siding package
- ♦ Vertical wall strapping for siding
- ♦ Urethane rigid roof insulation; urethane foam sealant and aluminum vapor barrier tape for sealing the insulation
- ♦ Edge and center bead pine boards for ceiling or walls
- ♦ 1x knotty pine v-groove interior wall boards
- ♦ Handcrafted mortise and tenon truss
- ♦ 4"x8" curved braces
- ♦ Additional interior stair material: treads, risers
- ♦ Interior railing material for loft & stair areas
- ♦ Optional Frame species: Douglas Fir
- ♦ Daylight basement materials: 2"x10" framing, 7/16" OSB wall sheathing, windows, doors, siding per plan
- ♦ Decorative exterior trusses, rafters, brackets, or pre-cut curved braces per plan
- ♦ Strip vent optional colors: white or brown
- ♦ HeatLock glazing on Andersen® window products