



2024 Camp & Cabin Series

Log Home Materials List



FLOOR SYSTEM

Sills: 2x6 PTSYP (graded #1 Pressure Treated Southern Yellow Pine)

Girders: 2x8 built up on job

Double headers: 2x8 Spruce

Felt paper: To cover double headers and sills

Floor joists: 2x8 Spruce 16" o.c. (On Center)

Hardware: Floor joist hangers and metal cross bridging

Subfloor: 5/8" OSB (Oriented Strand Board)

Porch and deck flooring: 5/4 radius edge PTSYP

Porch and deck framing: Floor joists, sills, and headers - PTSYP

Porch posts

EXTERIOR WALLS

Wall and gable logs: Eastern White Pine, Camp and Cabin grade, milled 6x8 'D' shaped tongue and groove pre-cut and numbered logs- kiln dried. Camp and Cabin grade logs have imperfections and a more rustic look

Log sealants: Log caulking, foam gaskets, pre-compressed corner pads, and 12" spiral spikes

Window and door jambs: Specially milled pine w/ screws

Log siding: Milled ship-lap log siding as needed for floor frame skirting, Eastern White Pine-kiln dried

Wall Braces: 6x6 or 6x8 as required with hardware

Splined posts: Specially milled 6x6 as required w/ hardware

2 sets of construction documents

Construction manual

CEILING

Ceiling joists: 2x8 Spruce 16" o.c.

Hardware: Ceiling joist hangers and metal cross bridging

Floor: 5/8" OSB

Posts and beams: Pine, Spruce, or LVL (laminated veneer lumber) as required with hardware

NOTE-Always refer to your individual price quote and Signed Order Form for specific material supplied with your home design.

ROOF

Double plate on top of log

Roof rafters: 2x8 or 2x10 Spruce 16" o.c.

Ridge beam*: LVL

Ridge beam support: 6x6 Pine or Spruce post, ridge to post connectors, rafter & heel connectors*

Roof sheathing: 5/8" OSB

Fascia: 1" Pine boards

Soffits: 1" Knotty Pine v-match boards

Porch rafters: 2x6 Spruce or Pine 16" o.c.

Porch beam: 6x6 Spruce or Pine

Vents: Ridge and soffit

*required for any building over 16' wide

WINDOWS AND EXTERIOR DOORS

Windows: Andersen® 400 Series Low-E4 glass Tilt-Wash and Casement windows with full screens

Flexi-frame windows

Colors: Sandtone, Terratone®, Forest Green, Dark Bronze, Black, Canvas, and White.

Patio Doors: Andersen Gliding and Hinged Patio Doors with screens, hardware, and key-locks.

Colors: White, Terratone®, Sandtone, and Forest Green.

Exterior doors: 3'0" x 6'8" pre-hung Therma-Tru® Smooth-Star® fiberglass door system with 20 year limited warranty

Exterior locksets

Exterior window and door trim: Random length Pine specially milled 2x4 radius edges

OPTIONAL MATERIALS

Extra log rows

11" LogHog screws

Interior wall framing material

1" Knotty Pine v-match boards for sheathing interior of roof, wall framing, and ceiling

Interior doors: Solid Pine with raised panel interior doors; pre-hung or sliding; with hardware and interior locksets as required

4x8 Spruce exposed beam ceiling joists with hangers and 2" v-match loft flooring

AdvanTech® subflooring and roof sheathing

Andersen® Window and Patio Door products: optional HeatLock® glazing. Note: Optional Andersen® items available at an upcharge

Engineer Stamped Plans and Energy Calcs